

SAFETY DATA SHEET 133-0XXX, DECOCOLOR, VARIOUS COLORS

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 133-0XXX, DECOCOLOR, VARIOUS COLORS

Chemical name UNIVERSAL COLORANT

Product number 133-0XXX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Ahsap Renklendirme

1.3. Details of the supplier of the safety data sheet

Supplier KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.

Aliağa Organize Sanayi Bölgesi

113 Sok. No:6 35800 Aliağa / İzmir

TURKEY

Tel: +90 232 621 50 01 info@kubilayboya.com www.kubilayboya.com

Manufacturer KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.

Aliağa Organize Sanayi Bölgesi

113 Sok. No:6 35800 Aliağa / İzmir

TURKEY

Tel: +90 232 621 50 01 info@kubilayboya.com www.kubilayboya.com

1.4. Emergency telephone number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336

Environmental hazards Not Classified

Human health Vapours and spray/mists in high concentrations are narcotic. Symptoms following

overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

Product has a defatting effect on skin.

Environmental The product is not expected to be hazardous to the environment.

133-0XXX, DECOCOLOR, VARIOUS COLORS

Physicochemical

The product is flammable and oxidising, and heating may generate vapours which may form explosive vapour/air mixtures.

2.2. Label elements

Pictogram





Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

Precautionary statements P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

 ${\sf P305+P351+P338\ IF\ IN\ EYES:\ Rinse\ cautiously\ with\ water\ for\ several\ minutes.\ Remove}$

contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/ container in accordance with national regulations.

Contains 1-METHOXY-2-PROPANOL

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

1-METHOXY-2-PROPANOL

60-80%

CAS number: 107-98-2 EC number: 203-539-1

Classification

Flam. Liq. 3 - H226 STOT SE 3 - H336

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information M

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.

133-0XXX, DECOCOLOR, VARIOUS COLORS

Inhalation Move affected person to fresh air at once. If breathing stops, provide artificial respiration.

When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention

immediately.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Remove

affected person from source of contamination. Rinse mouth thoroughly with water. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get

medical attention.

Skin contact Use appropriate hand lotion to prevent defatting and cracking of skin. Remove affected

person from source of contamination. Rinse immediately with plenty of water. Remove contaminated clothing. Get medical attention promptly if symptoms occur after washing.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause stomach pain or vomiting.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Alcohol-resistant foam. Carbon dioxide (CO2). Dry

chemicals, sand, dolomite etc. Do not use water, if avoidable.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is flammable. Heating may generate flammable vapours. Thermal decomposition

or combustion products may include the following substances: Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking,

sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and

contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Collect and place in suitable

waste disposal containers and seal securely. Label the containers containing waste and

contaminated materials and remove from the area as soon as possible.

6.3. Methods and material for containment and cleaning up

133-0XXX, DECOCOLOR, VARIOUS COLORS

Methods for cleaning up

Keep combustible materials away from spillage. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. Collect and dispose of spillage as indicated in Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Do not wear contact lenses. Avoid spilling. Avoid contact with skin and eyes. Eye wash facilities and emergency shower must be available when handling this product. During application and drying, solvent vapours will be emitted. Avoid inhalation of vapours. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store in tightly-closed, original container in a dry and cool place. Store under well-ventilated conditions at a temperature below 25°C. Keep away from heat, sparks and open flame. Keep away from food, drink and animal feeding stuffs.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

1-METHOXY-2-PROPANOL

 $\label{long-term} \mbox{Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 375 mg/m3(Sk)} \\ \mbox{Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 560 mg/m3(Sk)}$

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment









Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Contact lenses should not be worn when working with this chemical. The following protection should be worn: Chemical splash goggles.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Use engineering controls to reduce air contamination to permissible exposure level. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Provide eyewash station and safety shower. Wear apron or protective clothing in case of contact.

133-0XXX, DECOCOLOR, VARIOUS COLORS

Hygiene measures Provide eyewash station. Wash promptly if skin becomes contaminated. Promptly remove

non-impervious clothing that becomes contaminated. When using do not eat, drink or smoke.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Coloured liquid.

Colour Various (White, Yellow, Red, Blue, Green, Brown, Grey, Black Shades)

Odour Characteristic.

Initial boiling point and range >75°C @ 760 mm Hg

Flash point 31°C

Bulk density 1 ± 0.05 g/cm3, 20°C

Solubility(ies) Soluble in water.

Viscosity 15-20 sec, D4/20 @ °C

9.2. Other information

Other information Not available.

Volatile organic compound This product contains a maximum VOC content of 700 g/l.

Un-volatile content(%)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

products

Not known. No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Acids. Oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxides.

10.6. Hazardous decomposition products

Hazardous decomposition Oxides of carbon. Protection against nuisance dust must be used when the airborne

concentration exceeds 10 mg/m3.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Serious eye damage/irritation

Serious eye damage/irritation Not available.

133-0XXX, DECOCOLOR, VARIOUS COLORS

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity -

Not available.

development

Specific target organ toxicity - single exposure
STOT - single exposure
Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

133-0XXX, DECOCOLOR, VARIOUS COLORS

Disposal methods

Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263 UN No. (IMDG) 1263 UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group III
IMDG packing group III
ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

Hazard Identification Number 30

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. **Annex II of MARPOL 73/78**

and the IBC Code

SECTION 15: Regulatory information

133-0XXX, DECOCOLOR, VARIOUS COLORS

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and

This SDS is prepared based on the information received from the product raw material.

sources for data

Revision comments This is first issue.

Issued by Bahadır AKDAS

Revision date 03/10/2018

Revision 00

Supersedes date 03/10/2018

SDS number 20412

Hazard statements in full H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.