



SAFETY DATA SHEET
214-0057 PU OPTIMUM SANDING SEALER
Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 214-0057 PU OPTIMUM SANDING SEALER
Chemical name POLYURETHANE CLEAR SEALER (BASECOAT), POLIOL OF 2PACK POLIURETHANE SYSTEM
Product number 214-0057

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

Contact person Bahadır AKDAS (Mr) - arge@kubilayboya.com
(Certificate No:GBF01.28.10)

Manufacturer KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

1.4. Emergency telephone number

Emergency telephone KUBILAY BOYA : +90 232 621 50 01(office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Repr. 2 - H361 STOT SE 3 - H336 STOT RE 2 - H373
Environmental hazards Not Classified

214-0057 PU OPTIMUM SANDING SEALER

Human health

Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

2.2. Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H361 Suspected of damaging fertility or the unborn child.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.
 P201 Obtain special instructions before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take action to prevent static discharges.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P270 Do not eat, drink or smoke when using this product.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/ container in accordance with national regulations.

Contains

Toluene

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Toluene	40-60%
CAS number: 108-88-3	EC number: 203-625-9
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361 STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304	

214-0057 PU OPTIMUM SANDING SEALER

Xylene	1-5%
CAS number: 1330-20-7	EC number: 215-535-7
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Take off immediately all contaminated clothing and wash it before reuse. Rinse immediately with plenty of water. Get medical attention promptly if symptoms occur after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Slightly irritating.
Eye contact	Redness. Slightly irritating.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

214-0057 PU OPTIMUM SANDING SEALER

5.3. Advice for firefighters

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out. Avoid breathing fire gases or vapours. Fight fire from safe distance or protected location. Risk of re-ignition after fire has been extinguished.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Keep unnecessary and unprotected personnel away from the spillage. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. Do not touch or walk into spilled material.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Environmental Manager must be informed of all major spillages.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Place waste in labelled, sealed containers. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13. Clean contaminated objects and areas thoroughly, observing environmental regulations.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Use approved respirator if air contamination is above an acceptable level. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Good personal hygiene procedures should be implemented. Do not eat, drink or smoke when using this product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Protect from sunlight.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

214-0057 PU OPTIMUM SANDING SEALER

Toluene

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m³(Sk)

Xylene

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

WEL = Workplace Exposure Limit.

Ingredient comments WEL = Workplace Exposure Limits

Toluene (CAS: 108-88-3)

DNEL	Industry - Inhalation; Short term systemic effects: 384 mg/m ³ Consumer - Inhalation; Short term systemic effects: 226 mg/m ³ Workers - Dermal; Long term systemic effects: 384 mg/kg/day Consumer - Dermal; Long term systemic effects: 226 mg/kg Workers - Oral; Long term systemic effects: 192 mg/kg Consumer - Oral; Long term systemic effects: 8,13 mg/kg
PNEC	Fresh water; 0,68 mg/l marine water; 0,68 mg/l Water, Intermittent release; 0,68 mg/kg Sediment (Marinewater); 16,39 mg/kg STP; 13,61 mg/l

Xylene (CAS: 1330-20-7)

DNEL	Workers - Dermal; Short term systemic effects: 442 mg/kg/day Workers - Dermal; Long term systemic effects: 221 mg/kg/day
PNEC	Fresh water; 0,327 mg/l Sediment (Freshwater); 12,46 mg/kg Soil; 2,31 mg/kg marine water; 0,327 mg/l Sediment (Marinewater); 12,46 mg/kg STP; 6,58 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

214-0057 PU OPTIMUM SANDING SEALER

Hand protection	Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. To protect hands from chemicals, gloves should comply with European Standard EN374.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact.
Hygiene measures	Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. Do not eat, drink or smoke when using this product.
Respiratory protection	Wear a respirator fitted with the following cartridge: Organic vapour filter. Gas and combination filter cartridges should comply with European Standard EN14387. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Slightly viscous liquid.
Colour	Colourless.
Odour	Characteristic.
Odour threshold	No information available.
Melting point	No information available.
Initial boiling point and range	>35°C @ 760 mm Hg
Flash point	<23°C
Flammability (solid, gas)	No information available.
Upper/lower flammability or explosive limits	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	No information available.
Bulk density	1,08 ±0,005 g/cm ³ , 20°C
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	40" - 50" D6 @ 25°C

214-0057 PU OPTIMUM SANDING SEALER

Explosive properties There are no chemical groups present in the product that are associated with explosive properties.

Oxidising properties There are no chemical groups present in the product that are associated with oxidising properties.

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not known. No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxides.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 110,000.0

Acute toxicity - inhalation

ATE inhalation (gases ppm) 450,000.0

ATE inhalation (vapours mg/l) 1,100.0

ATE inhalation (dusts/mists mg/l) 150.0

Skin corrosion/irritation

Skin corrosion/irritation Slightly irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

214-0057 PU OPTIMUM SANDING SEALER

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Genotoxicity - in vivo Not available.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity - development Not available.

Specific target organ toxicity - single exposure

STOT - single exposure Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

Product has a defatting effect on skin.

Eye contact

Symptoms following overexposure may include the following: Redness. Pain. Slightly irritating.

Route of exposure

Inhalation Skin absorption

Medical symptoms

Irritation of eyes and mucous membranes.

SECTION 12: Ecological information

Ecotoxicity

The product is not expected to be hazardous to the environment. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Ecological information on ingredients.

Toluene

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 6.3 ;Pimephales promelas mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 11.3 ; Daphnia magna mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 125-160 ; Scenedesmus subspicatus mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

214-0057 PU OPTIMUM SANDING SEALER

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

214-0057 PU OPTIMUM SANDING SEALER

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Hazard Identification Number 33
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
IATA: International Air Transport Association.
IMDG: International Maritime Dangerous Goods.
CAS: Chemical Abstracts Service.
EC₅₀: 50% of maximal Effective Concentration.
LC₅₀: Lethal Concentration to 50 % of a test population.
LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
ATE: Acute Toxicity Estimate.
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.

Key literature references and sources for data This SDS is prepared based on the information received from the product raw material.
Source: European Chemicals Agency, <http://echa.europa.eu/>

Revision comments This is the first issue.

Issued by Bahadır AKDAS - arge@kubilayboya.com

Revision date 10/12/2020

Revision 03

Supersedes date 10/12/2020

SDS number 20512

214-0057 PU OPTIMUM SANDING SEALER

Hazard statements in full

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.