

**SAFETY DATA SHEET****261-XXXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS**

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

<b>Product name</b>	261-XXXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS
<b>Chemical name</b>	POLYURETHANE PIGMENTED TOPCOAT ENAMEL, POLIOL OF 2PACK POLIURETHANE SYSTEM
<b>Product number</b>	261-XXXXY

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

<b>Identified uses</b>	Wood Coating
------------------------	--------------

**1.3. Details of the supplier of the safety data sheet**

<b>Supplier</b>	KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI. Aliağa Organize Sanayi Bölgesi 113 Sok. No:6 35800 Aliağa / İzmir TURKEY  Tel: +90 232 621 50 01 info@kubilayboya.com www.kubilayboya.com
<b>Contact person</b>	Bahadır AKDAS (Mr) - arge@kubilayboya.com (Certificate No:01.79.05)
<b>Manufacturer</b>	KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI. Aliağa Organize Sanayi Bölgesi 113 Sok. No:6 35800 Aliağa / İzmir TURKEY  Tel: +90 232 621 50 01 info@kubilayboya.com www.kubilayboya.com

**1.4. Emergency telephone number**

<b>Emergency telephone</b>	KUBILAY BOYA : +90 232 621 50 01 (office hours)
----------------------------	---

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification (EC/1272/2008)**

<b>Physical hazards</b>	Flam. Liq. 2 - H225
<b>Health hazards</b>	Acute Tox. 4 - H332 Skin Irrit. 2 - H315
<b>Environmental hazards</b>	Not Classified

## 261-XXXV WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS

### Human health

Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. The product is irritating to eyes and skin.

### Environmental


The product is not expected to be hazardous to the environment.

### Physicochemical

The product is flammable. Heating may generate flammable vapours.

### 2.2. Label elements

#### Pictogram



#### Signal word

Danger

#### Hazard statements

H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H332 Harmful if inhaled.

#### Precautionary statements

P102 Keep out of reach of children.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P270 Do not eat, drink or smoke when using this product.  
P280 Wear protective clothing, gloves, eye and face protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P302+P352 IF ON SKIN: Wash with plenty of water.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P370+P378 In case of fire: Use dry powder, dry sand or dry earth to extinguish.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P501 Dispose of contents/ container in accordance with national regulations.

#### Contains

XYLENE

### 2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>XYLENE</b>		<b>25-40%</b>
CAS number: 1330-20-7		EC number: 215-535-7
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315		

**261-XXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS**

<b>BUTANONE</b>		<b>5-10%</b>
CAS number: 78-93-3	EC number: 201-159-0	
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		
<b>BUTYL ACETATE -norm</b>		<b>1-5%</b>
CAS number: 123-86-4	EC number: 204-658-1	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336		
<b>2-METHOXY-1-METHYLETHYL ACETATE</b>		<b>1-5%</b>
CAS number: 108-65-6	EC number: 203-603-9	
<b>Classification</b> Flam. Liq. 3 - H226		
<b>TOLUENE</b>		<b>1-5%</b>
CAS number: 108-88-3	EC number: 203-625-9	
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361 STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304		

The full text for all hazard statements is displayed in Section 16.

**Composition comments**      The data shown are in accordance with the latest EC Directives. Meets BS EN 71-3:2013+A1:2014 standards.

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

## 261-XXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS

**Skin contact** Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing.

**Eye contact** Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

### **4.2. Most important symptoms and effects, both acute and delayed**

**Inhalation** Vapours may cause headache, fatigue, dizziness and nausea.

**Ingestion** May cause stomach pain or vomiting.

**Skin contact** Skin irritation.

**Eye contact** Irritation of eyes and mucous membranes.

### **4.3. Indication of any immediate medical attention and special treatment needed**

**Notes for the doctor** No specific recommendations.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable extinguishing media** Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards** Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Risk of explosion if heated.

### **5.3. Advice for firefighters**

**Protective actions during firefighting** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

### **6.2. Environmental precautions**

**Environmental precautions** Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### **6.3. Methods and material for containment and cleaning up**

**Methods for cleaning up** Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. Do not touch or walk into spilled material. Small Spillages: Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

### **6.4. Reference to other sections**

## 261-XXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Avoid inhalation of vapours and spray/mists.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Keep away from heat, sparks and open flame. Keep away from food, drink and animal feeding stuffs.

**Storage class** Flammable liquid storage.

#### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

##### BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m<sup>3</sup>(Sk)

##### BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

##### 2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m<sup>3</sup>(Sk)

##### TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m<sup>3</sup>(Sk)

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

##### Protective equipment



## 261-XXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS

<b>Appropriate engineering controls</b>	Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.
<b>Eye/face protection</b>	Wear chemical splash goggles.
<b>Hand protection</b>	Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.
<b>Hygiene measures</b>	Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
<b>Respiratory protection</b>	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Slightly viscous liquid.
<b>Colour</b>	Various colours.
<b>Odour</b>	Characteristic.
<b>Initial boiling point and range</b>	>35°C @ 760 mm Hg
<b>Flash point</b>	< 25°C
<b>Bulk density</b>	1,12 ± 0,05 g/cm <sup>3</sup> , 20°C
<b>Solubility(ies)</b>	Insoluble in water.
<b>Viscosity</b>	90 - 110 sec, D4/20 @ °C

#### 9.2. Other information

<b>Other information</b>	Not available.
<b>Volatile organic compound</b>	This product contains a maximum VOC content of 500 g/l.
<b>Un-volatile content(%)</b>	

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
-------------------	---

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Not known. No potentially hazardous reactions known.
---	--

#### 10.4. Conditions to avoid

## 261-XXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.

### 10.5. Incompatible materials

**Materials to avoid** No specific material or group of materials is likely to react with the product to produce a hazardous situation.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m<sup>3</sup>.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 333,333.0

#### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 1,363,636.0

**ATE inhalation (vapours mg/l)** 3,333.0

**ATE inhalation (dusts/mists mg/l)** 455.0

#### Germ cell mutagenicity

**Genotoxicity - in vitro** No information available.

**Genotoxicity - in vivo** No information available.

#### Carcinogenicity

**Carcinogenicity** No information available.

#### Reproductive toxicity

**Reproductive toxicity - fertility** No information available.

**Reproductive toxicity - development** No information available.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** No information available.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** No information available.

### General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

#### Inhalation

Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.

#### Ingestion

Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin. Harmful in contact with skin.

#### Eye contact

Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

#### Route of entry

Inhalation Skin absorption

## 261-XXX XY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS

**Medical symptoms** Irritation of eyes and mucous membranes.

### SECTION 12: Ecological Information

**Ecotoxicity** The product is not expected to be hazardous to the environment.

#### 12.1. Toxicity

##### Ecological information on ingredients.

##### XYLENE

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 26700 ; Pimephales promelas mg/l, Fish
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 150.000 ; Daphnia magna mg/l, Daphnia magna

##### BUTYL ACETATE -norm

<b>Acute toxicity - fish</b>	LC <sub>50</sub> , 96 hours: 18 mg/l Pimephales promelas mg/l, Fish
<b>Acute toxicity - aquatic invertebrates</b>	EC <sub>50</sub> , 48 hours: 72.8 mg/l Daphnia magna mg/l, Daphnia magna
<b>Acute toxicity - aquatic plants</b>	IC <sub>50</sub> , 72 hours: 674.7 mg/l Scenedesmus subspicatus mg/l, Algae

#### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

##### Ecological information on ingredients.

##### XYLENE

**Bioaccumulative potential** No data available on bioaccumulation.

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** No information required.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

<b>General information</b>	When handling waste, the safety precautions applying to handling of the product should be considered.
<b>Disposal methods</b>	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

### SECTION 14: Transport information



## 261-XXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS

### 14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

### 14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels



### 14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

### 14.6. Special precautions for user

Hazard Identification Number (ADR/RID) 30

Tunnel restriction code (D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78  
and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).  
EH40/2005 Workplace exposure limits.

**261-XXXY WINCOPOL PU MATTE/ SILK MATTE TOPCOAT, VARIOUS COLOURS**

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

**SECTION 16: Other information**

**Key literature references and sources for data** This SDS is prepared based on the information received from the product raw material.

**Revision comments** This is first issue.

**Issued by** Bahadır AKDAS

**Revision date** 01/09/2016

**Revision** 00

**Supersedes date** 01/09/2016

**SDS number** 20312

**Hazard statements in full**

H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child if swallowed.  
H373 May cause damage to organs through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.