

**SAFETY DATA SHEET****295-0005 VIP 2K ULTRA GLOSSY VARNISH**

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name 295-0005 VIP 2K ULTRA GLOSSY VARNISH
Chemical name POLYURETHANE TOPCOAT VARNISH, POLIOL OF 2PACK POLIURETHANE SYSTEM
Product number 295-0005

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Wood Coating

1.3. Details of the supplier of the safety data sheet

Supplier KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

Contact person Bahadır AKDAS (Mr) - arge@kubilayboya.com
(Certificate No:01.79.05)

Manufacturer KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

1.4. Emergency telephone number

Emergency telephone KUBILAY BOYA : +90 232 621 50 01 (office hours)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (EC/1272/2008)**

Physical hazards Flam. Liq. 3 - H226
Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315
Environmental hazards Not Classified

295-0005 VIP 2K ULTRA GLOSSY VARNISH


Human health Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. The product is irritating to eyes and skin.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical The product is flammable. Heating may generate flammable vapours.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H332 Harmful if inhaled.

Precautionary statements P102 Keep out of reach of children.
P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302+P352 IF ON SKIN: Wash with plenty of water.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.
P501 Dispose of contents/ container in accordance with national regulations.

Contains XYLENE, ISOBUTYL METHYL KETONE

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

XYLENE	25-40%
CAS number: 1330-20-7	EC number: 215-535-7
Classification	
Flam. Liq. 3 - H226	
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	

295-0005 VIP 2K ULTRA GLOSSY VARNISH

BUTYL ACETATE -norm	5-10%
CAS number: 123-86-4	EC number: 204-658-1
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	
ISOBUTYL METHYL KETONE	1-5%
CAS number: 108-10-1	EC number: 203-550-1
Classification	
Flam. Liq. 2 - H225	
Acute Tox. 4 - H332	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
2-BUTOXYETHANOL	1-5%
CAS number: 111-76-2	EC number: 203-905-0
Classification	
Acute Tox. 4 - H302	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	

The full text for all hazard statements is displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Skin irritation.

295-0005 VIP 2K ULTRA GLOSSY VARNISH

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Risk of explosion if heated.

5.3. Advice for firefighters

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. Do not touch or walk into spilled material. Small Spillages: Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Avoid inhalation of vapours and spray/mists.

7.2. Conditions for safe storage, including any incompatibilities

295-0005 VIP 2K ULTRA GLOSSY VARNISH

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Keep away from heat, sparks and open flame. Keep away from food, drink and animal feeding stuffs.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ISOBUTYL METHYL KETONE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 208 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 416 mg/m³(Sk)

2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk)

Short-term exposure limit (15-minute): WEL 50 ppm(Sk)

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex). The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

295-0005 VIP 2K ULTRA GLOSSY VARNISH

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Slightly viscous liquid.
Colour	Colourless.
Odour	Characteristic.
Initial boiling point and range	>35°C @ mm Hg
Flash point	> 25°C
Bulk density	1 ± 0,05 g/cm ³ , 20°C
Solubility(ies)	Insoluble in water.
Viscosity	40 - 45 sec, D4/20 @ °C

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 390 g/l.
Un-volatile content(%)	

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not known. No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 250,000.0

Acute toxicity - dermal

295-0005 VIP 2K ULTRA GLOSSY VARNISH

ATE dermal (mg/kg) 349,762.0

Acute toxicity - inhalation

ATE inhalation (gases ppm) 1,345,291.0

ATE inhalation (vapours mg/l) 3,288.0

ATE inhalation (dusts/mists mg/l) 448.0

Germ cell mutagenicity

Genotoxicity - in vitro No information available.

Genotoxicity - in vivo No information available.

Carcinogenicity

Carcinogenicity No information available.

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Reproductive toxicity - development No information available.

Specific target organ toxicity - single exposure

STOT - single exposure No information available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin. Harmful in contact with skin.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

Route of entry Inhalation Skin absorption

Medical symptoms Irritation of eyes and mucous membranes.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Ecological information on ingredients.

XYLENE

Acute toxicity - fish LC₅₀, 96 hours: 26700 ; Pimephales promelas mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 150.000 ; Daphnia magna mg/l, Daphnia magna

295-0005 VIP 2K ULTRA GLOSSY VARNISH

BUTYL ACETATE -norm

Acute toxicity - fish	LC ₅₀ , 96 hours: 18 mg/l Pimephales promelas mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 72.8 mg/l Daphnia magna mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 674.7 mg/l Scenedesmus subspicatus mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

XYLENE

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information	When handling waste, the safety precautions applying to handling of the product should be considered.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT RELATED MATERIAL
Proper shipping name (IMDG)	PAINT RELATED MATERIAL
Proper shipping name (ICAO)	PAINT RELATED MATERIAL
Proper shipping name (ADN)	PAINT RELATED MATERIAL

295-0005 VIP 2K ULTRA GLOSSY VARNISH

14.3. Transport hazard class(es)

ADR/RID class	3
IMDG class	3
ICAO class/division	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Hazard Identification Number 30
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data This SDS is prepared based on the information received from the product raw material.

Revision comments This is first issue.

Issued by Bahadır AKDAS

Revision date 01/09/2016

295-0005 VIP 2K ULTRA GLOSSY VARNISH

Revision	00
Supersedes date	01/09/2016
SDS number	20310
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H302 Harmful if swallowed. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.