



SAFETY DATA SHEET

314-0036 ACRYLIC SEALER VARNISH

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 314-0036 ACRYLIC SEALER VARNISH
Chemical name POLIOL OF 2 PACK ACRYLIC SYSTEM
Product number 314-0036

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Wood coating.

1.3. Details of the supplier of the safety data sheet

Supplier KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

Contact person Bahadır AKDAS (Mr) - arge@kubilayboya.com
(Certificate No:01.79.05)

Manufacturer KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

1.4. Emergency telephone number

Emergency telephone KUBILAY BOYA : +90 232 621 50 01 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361 STOT SE 3 - H336 STOT RE 2 - H373
Environmental hazards Not Classified

314-0036 ACRYLIC SEALER VARNISH

Human health Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical The product is flammable. Heating may generate flammable vapours.

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

- P102 Keep out of reach of children.
- P201 Obtain special instructions before use.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with national regulations.

Contains BUTYL ACETATE -norm, ACETONE, TOLUENE

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

BUTYL ACETATE -norm	25-40%
CAS number: 123-86-4	EC number: 204-658-1
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	

314-0036 ACRYLIC SEALER VARNISH

ACETONE	10-20%
CAS number: 67-64-1	EC number: 200-662-2
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R66 R67
TOLUENE	10-20%
CAS number: 108-88-3	EC number: 203-625-9
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361 STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412	
XYLENE	5-10%
CAS number: 1330-20-7	EC number: 215-535-7
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove contaminated clothing.

314-0036 ACRYLIC SEALER VARNISH

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause stomach pain or vomiting.

Skin contact Skin irritation.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out. Avoid breathing fire gases or vapours. Fight fire from safe distance or protected location. Risk of re-ignition after fire has been extinguished.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Use air-supplied respirator, gloves and protective goggles.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

314-0036 ACRYLIC SEALER VARNISH

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents.

Storage class

Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m³(Sk)

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

WEL = Workplace Exposure Limit

Ingredient comments

WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear apron or protective clothing in case of contact.

314-0036 ACRYLIC SEALER VARNISH

Hygiene measures Provide eyewash station. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection Wear a respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Slightly viscous liquid.
Colour	Colourless.
Odour	Characteristic.
Initial boiling point and range	>35°C @ 760 mm Hg
Flash point	< 23°C
Bulk density	0,98 ±0,005 g/cm ³ , 20°C
Solubility(ies)	Insoluble in water.
Viscosity	35" - 40" D6 @ 25°C

9.2. Other information

Other information	Not available.
Volatile organic compound	This product contains a maximum VOC content of 590 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not known. No potentially hazardous reactions known.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong oxides.
---------------------------	----------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ .
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg)	1,428,571.0
---------------------------	-------------

314-0036 ACRYLIC SEALER VARNISH

Acute toxicity - inhalation

ATE inhalation (gases ppm) 5,844,156.0

ATE inhalation (vapours mg/l) 14,286.0

ATE inhalation (dusts/mists mg/l) 1,948.0

Serious eye damage/irritation

Serious eye damage/irritation Not available.

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Genotoxicity - in vivo Not available.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Specific target organ toxicity - single exposure

STOT - single exposure Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.

Ingestion

Gastrointestinal symptoms, including upset stomach.

Skin contact

Product has a defatting effect on skin. May cause allergic contact eczema. Harmful in contact with skin.

Eye contact

Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

SECTION 12: Ecological Information

Ecotoxicity

The product is not expected to be hazardous to the environment.

12.1. Toxicity

Ecological information on ingredients.

TOLUENE

Acute toxicity - fish LC₅₀, 96 hours: 6.3 ;Pimephales promelas mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 11.3 ; Daphnia magna mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 125-160 ; Scenedesmus subspicatus mg/l, Algae

12.2. Persistence and degradability

314-0036 ACRYLIC SEALER VARNISH

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class	3
IMDG class	3
ICAO class/division	3

Transport labels



14.4. Packing group

ADR/RID packing group II

314-0036 ACRYLIC SEALER VARNISH

IMDG packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Hazard Identification Number 30
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data This SDS is prepared based on the information received from the product raw material.

Revision comments This is first issue.

Issued by Bahadır AKDAS

Revision date 11/05/2016

Revision 00

Supersedes date 11/05/2016

SDS number 20280

314-0036 ACRYLIC SEALER VARNISH

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H361 Suspected of damaging fertility or the unborn child if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.