



SAFETY DATA SHEET

402-XXXX RAPID PRIMER, VARIOUS COLOURS

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 402-XXXX RAPID PRIMER, VARIOUS COLOURS
Chemical name FAST DRYING PRIMER
Product number 402-XXXX

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

Contact person Bahadır AKDAS (Mr) - arge@kubilayboya.com
(Certificate No:01.79.05)

Manufacturer KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.
Aliağa Organize Sanayi Bölgesi
113 Sok. No:6
35800 Aliağa / İzmir
TURKEY

Tel: +90 232 621 50 01
info@kubilayboya.com
www.kubilayboya.com

1.4. Emergency telephone number

Emergency telephone KUBILAY BOYA : +90 232 621 50 01 (office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361 STOT SE 3 - H336 STOT RE 2 - H373
Environmental hazards Not Classified

2.2. Label elements

402-XXXX RAPID PRIMER, VARIOUS COLOURS**Pictogram****Signal word**

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H361 Suspected of damaging fertility or the unborn child.
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.
 P201 Obtain special instructions before use.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe vapour/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P501 Dispose of contents/container in accordance with national regulations.

Contains

TOLUENE

2.3. Other hazards**SECTION 3: Composition/information on ingredients****3.2. Mixtures****TOLUENE****20-25%**

CAS number: 108-88-3

EC number: 203-625-9

Classification

Flam. Liq. 2 - H225
 Skin Irrit. 2 - H315
 Eye Irrit. 2 - H319
 Repr. 2 - H361
 STOT SE 3 - H336
 STOT RE 2 - H373
 Asp. Tox. 1 - H304
 Aquatic Chronic 3 - H412

402-XXXX RAPID PRIMER, VARIOUS COLOURS

XYLENE	1-5%
CAS number: 1330-20-7	EC number: 215-535-7
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Do not induce vomiting. Remove affected person from source of contamination. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Coughing, chest tightness, feeling of chest pressure. Nausea, vomiting. Exhaustion and weakness.
Ingestion	Nausea, vomiting. Drowsiness, dizziness, disorientation, vertigo.
Skin contact	Skin irritation.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations.
-----------------------------	------------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO). May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

5.3. Advice for firefighters

402-XXXX RAPID PRIMER, VARIOUS COLOURS

Protective actions during firefighting	Avoid breathing fire gases or vapours. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. Ventilate closed spaces before entering them. Move containers from fire area if it can be done without risk. Risk of re-ignition after fire has been extinguished. Do not use water jet as an extinguisher, as this will spread the fire.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. For waste disposal, see Section 13.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Eliminate all sources of ignition. Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours.
--------------------------	---

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.
Storage class	Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m³(Sk)

402-XXXX RAPID PRIMER, VARIOUS COLOURS

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

Hygiene measures

Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Slightly viscous liquid.
Colour	Various colours.
Odour	Characteristic.
Initial boiling point and range	>75°C @ 760 mm Hg
Flash point	<23°C
Bulk density	1,5 ±0,05 g/cm ³ , 20C
Solubility(ies)	Insoluble in water.
Viscosity	110 - 130 s @ D4 / 20°C

9.2. Other information

Other information	No information required.
Volatile organic compound	This product contains a maximum VOC content of 320 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

402-XXXX RAPID PRIMER, VARIOUS COLOURS

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat. Avoid contact with the following materials: Oxidising agents. Reducing agents.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - dermal

ATE dermal (mg/kg) 1,100,000.0

Acute toxicity - inhalation

ATE inhalation (gases ppm) 4,500,000.0

ATE inhalation (vapours mg/l) 11,000.0

ATE inhalation (dusts/mists mg/l) 1,500.0

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Genotoxicity - in vivo Not available.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity - development Not available.

Specific target organ toxicity - single exposure

STOT - single exposure Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system/lungs.

402-XXXX RAPID PRIMER, VARIOUS COLOURS

Ingestion	Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.
Skin contact	Harmful: danger of serious damage to health by prolonged exposure in contact with skin.
Eye contact	Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.
Acute and chronic health hazards	Swallowing concentrated chemical may cause severe internal injury.
Route of entry	Inhalation Ingestion. Skin and/or eye contact
Target organs	Respiratory system, lungs
Medical symptoms	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
Medical considerations	Skin disorders and allergies.

SECTION 12: Ecological Information

Ecotoxicity No data on possible environmental effects have been found.

12.1. Toxicity

Acute toxicity - fish LC₅₀, 96 hours: >100 mg/l, Fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >100 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: >100 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product is miscible with water and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

402-XXXX RAPID PRIMER, VARIOUS COLOURS

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT RELATED MATERIAL

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) FLAMMABLE LIQUID, NOS

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ADN packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78
and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

402-XXXX RAPID PRIMER, VARIOUS COLOURS

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Guidance	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Key literature references and sources for data This SDS is prepared based on the information received from the product raw material.

Revision comments This is first issue.

Issued by Bahadır AKDAS

Revision date 12/04/2016

Revision 00

Supersedes date 12/04/2016

SDS number 20253

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H361 Suspected of damaging fertility or the unborn child if swallowed.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.