

## TECHNICAL DATA SHEET

Dök.No: ÜRT-TDS-186 Yay.Tar.: 03.07.2020 Rev. No: REVİZYON-00 Rev.Tar.: 03.07.2020 Sayfa: 1/1

PRODUCT	STRIP-COAT LSR HFT Non-Sag Water Based Peelable Coating
PRODUCT CODE	808-0043
DESCRIPTION AND APPLICATION FIELDS	It is a water-based, transparent peel-off coating designed to protect the painted furniture in the marine group with a thick layer, without being exposed to the stack load, for temporary protection against water and surface impacts.  In addition, it can also be used to provide temporary protection on surfaces that will not be exposed to stack such as door, window frames, glass, wood laminate, parquet, marble, granite surfaces etc. during the construction or renovation phase.
TECHNICAL PROPERTIES	Density (g/cm3; 20°C) 1,08 ±0,05
PROPERTIES	Appliable up to 300 micron film thickness  Fast Dry  Non-sag  Easy Peelable
DILUTION RATIO	It's ready to use in delivery form, no need to dilute for thick applications. But if thinner film thickness is desired, it can be thinned with 10-15% water depending on the desired thickness.

## APPLICATION METHOD:

Before applying, the product should mix slowly without foaming until it becomes homogeneous in the package.

It is applied as a cross with two passes (max 300 micron (325 g/m2)) on the surfaces that totally dry and dust free.

When applied as a layer with a thickness of 45-50 micron dry film, 9-10 m2 area can be coated for 1 lt by applying 90-100 g/m2 (except losses).

## STORAGE:

Products will remain stable for at least 12 months when stored in its original pack in a dry place at storage temperatures between 5-35 °C.

It's recommended to read SDS before applications.

Important Note: This information is based on our present state of knowledge and is intended to provide general notes on Kubilay Products and their uses. However without garantee as conditions and methods of end users are beyond our control. We recommend that end users determine the suitability of the materials before adapting them on a commercial scale.