

SAFETY DATA SHEET 812-1002 VERNIPOL POLYESTER SOFT PRIMER, WHITE

Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 812-1002 VERNIPOL POLYESTER SOFT PRIMER, WHITE

Chemical name UNSATURATED POLYESTER SYSTEM

Product number 812-1002

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Wood Coating

1.3. Details of the supplier of the safety data sheet

Supplier KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.

Aliağa Organize Sanayi Bölgesi

113 Sok. No:6 35800 Aliağa / İzmir

TURKEY

Tel: +90 232 621 50 01 info@kubilayboya.com www.kubilayboya.com

Contact person Bahadır AKDAS (Mr) - arge@kubilayboya.com

(Certificate No:GBF01.28.10)

Manufacturer KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.

Aliağa Organize Sanayi Bölgesi

113 Sok. No:6 35800 Aliağa / İzmir

TURKEY

Tel: +90 232 621 50 01 info@kubilayboya.com www.kubilayboya.com

1.4. Emergency telephone number

Emergency telephone KUBILAY BOYA: +90 232 621 50 01(office hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361 STOT RE 1 - H372

Environmental hazards Not Classified

Human health Vapours and spray/mists in high concentrations are narcotic. Symptoms following

overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

Irritating to eyes. Harmful by inhalation.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical The product is flammable. Heating may generate flammable vapours.

2.2. Label elements

Hazard pictograms







Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

P102 Keep out of reach of children.

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take action to prevent static discharges.

P260 Do not breathe vapour/ spray.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with national regulations.

Contains

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

Styrene

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Styrene 10-20%

CAS number: 100-42-5 EC number: 202-851-5

Classification

Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361 STOT SE 3 - H335 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Never give anything by mouth to an unconscious person. Get medical attention if

any discomfort continues.

Inhalation Place unconscious person on their side in the recovery position and ensure breathing can

take place. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention if any discomfort continues.

Ingestion Rinse mouth thoroughly with water. Give milk instead of water if readily available. Keep

affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.

Show this Safety Data Sheet to the medical personnel.

Skin contact Immediately remove contaminated clothing. Rinse immediately with plenty of water. Remove

contaminated clothing.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause stomach pain or vomiting.

Skin contact Slightly irritating.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctorNo specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry

powder. Dry chemicals, sand, dolomite etc.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Risk of explosion if heated. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out. Avoid breathing fire gases or vapours. Risk of re-ignition after fire has been extinguished. Do not use water jet as an extinguisher, as this will spread the fire.

Special protective equipment for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions

Avoid discharge into drains or watercourses or onto the ground. Environmental Manager must be informed of all major spillages.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Place waste in labelled, sealed containers. Wash thoroughly after dealing with a spillage. Dispose of waste via a licensed waste disposal contractor.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep away from heat, sparks and open flame. Avoid spilling. Provide adequate ventilation. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Do not wear contact lenses. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original

container in a dry, cool and well-ventilated place. Protect from sunlight.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Styrene

Long-term exposure limit (8-hour TWA): WEL 100 ppm 430 mg/m³ Short-term exposure limit (15-minute): WEL 250 ppm 1080 mg/m³ WEL = Workplace Exposure Limit.

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment









Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber

(natural, latex).

The breakthrough time for any glove material may be different for different glove manufacturers. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Wear a respirator fitted with the following cartridge: Organic vapour filter. Gas and combination filter cartridges should comply with European Standard EN14387.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Slightly viscous liquid.

Colour White.

Odour Characteristic.

Revision date: 02/11/2021 Revision: 00 Supersedes date: 02/11/2021

812-1002 VERNIPOL POLYESTER SOFT PRIMER, WHITE

Odour threshold No information available. No information available. Melting point No information available. Initial boiling point and range

Flash point >25°C

Flammability (solid, gas) No information available. Upper/lower flammability or No information available.

explosive limits

Vapour pressure No information available.

Vapour density No information available.

Relative density No information available.

 $1,37 \pm 0,05$ g/cm 3, 20C **Bulk density**

Solubility(ies) No information available.

No information available. Partition coefficient

Auto-ignition temperature No information available.

Decomposition Temperature No information available.

Viscosity 60 - 70 " D6/20C @ °C

Explosive properties There are no chemical groups present in the product that are associated with explosive

properties.

Oxidising properties There are no chemical groups present in the product that are associated with oxidising

properties.

9.2. Other information

Other information Not available.

Volatile organic compound This product contains a maximum VOC content of 10 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not known. No potentially hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxides.

10.6. Hazardous decomposition products

Revision date: 02/11/2021 Revision: 00 Supersedes date: 02/11/2021

812-1002 VERNIPOL POLYESTER SOFT PRIMER, WHITE

Hazardous decomposition

Thermal decomposition or combustion products may include the following substances: Oxides

products

of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 59.6

Skin corrosion/irritation

Skin corrosion/irritation Slightly irritating.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisationBased on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro

Not available.

Genotoxicity - in vivo

Not available.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity -

development

Not available.

Specific target organ toxicity - single exposure

STOT - single exposure Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure

Not available.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent

health problems.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing. Harmful by inhalation.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Repeated exposure may cause skin dryness or cracking. Slightly irritating.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain.

Route of exposure Inhalation Skin absorption

Medical symptoms Irritation of eyes and mucous membranes.

SECTION 12: Ecological information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity No information available.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility The product is water-soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects No information required.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into

containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name

PAINT RELATED MATERIAL

(ADR/RID)

Proper shipping name (IMDG) PAINT RELATED MATERIAL

Proper shipping name (ICAO) PAINT RELATED MATERIAL

Proper shipping name (ADN) PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR/RID class 3

IMDG class 3

ICAO class/division 3

Transport labels



14.4. Packing group

ADR/RID packing group Ш IMDG packing group Ш ICAO packing group Ш

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Hazard Identification Number

(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by

Road.

IATA: International Air Transport Association.

IMDG: International Maritime Dangerous Goods.

CAS: Chemical Abstracts Service.

EC₅: 50% of maximal Effective Concentration.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

ATE: Acute Toxicity Estimate.

PBT: Persistent, Bioaccumulative and Toxic substance.

vPvB: Very Persistent and Very Bioaccumulative.

Revision date: 02/11/2021 Revision: 00 Supersedes date: 02/11/2021

812-1002 VERNIPOL POLYESTER SOFT PRIMER, WHITE

Key literature references and

This SDS is prepared based on the information received from the product raw material.

sources for data

Source: European Chemicals Agency, http://echa.europa.eu/

Revision comments

This is the first issue.

Issued by

Bahadır AKDAS - arge@kubilayboya.com

Revision date

02/11/2021

Revision

00

Supersedes date

02/11/2021

SDS number

20563

Hazard statements in full

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H372 Causes damage to organs through prolonged or repeated exposure if swallowed.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.