

**SAFETY DATA SHEET****334-0026 VIP FAST ACRYL SEALER VARNISH**

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Product name** 334-0026 VIP FAST ACRYL SEALER VARNISH  
**Chemical name** POLYOL OF 2 PACK ACRYLIC SYSTEM  
**Product number** 334-0026

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Wood coating

**1.3. Details of the supplier of the safety data sheet**

**Supplier** KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.  
Aliağa Organize Sanayi Bölgesi  
113 Sok. No:6  
35800 Aliağa / İzmir  
TURKEY

Tel: +90 232 621 50 01  
info@kubilayboya.com  
www.kubilayboya.com

**Contact person** Bahadır AKDAS (Mr) - arge@kubilayboya.com  
(Certificate No:01.79.05)

**Manufacturer** KUBILAY KIMYA VE BOYA SAN.TIC.LTD.STI.  
Aliağa Organize Sanayi Bölgesi  
113 Sok. No:6  
35800 Aliağa / İzmir  
TURKEY

Tel: +90 232 621 50 01  
info@kubilayboya.com  
www.kubilayboya.com

**1.4. Emergency telephone number**

**Emergency telephone** KUBILAY BOYA : +90 232 621 50 01 (office hours)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification**

**Physical hazards** Flam. Liq. 2 - H225

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Repr. 2 - H361 STOT SE 3 - H336 STOT RE 2 - H373

**Environmental hazards** Not Classified

**2.2. Label elements**

**334-0026 VIP FAST ACRYL SEALER VARNISH****Pictogram****Signal word**

Danger

**Hazard statements**

H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H361 Suspected of damaging fertility or the unborn child.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**Precautionary statements**

P102 Keep out of reach of children.  
 P201 Obtain special instructions before use.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P243 Take precautionary measures against static discharge.  
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P270 Do not eat, drink or smoke when using this product.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P501 Dispose of contents/container in accordance with national regulations.

**Contains**

BUTYL ACETATE -norm, TOLUENE, ACETONE, ETHYL ACETATE

**2.3. Other hazards****SECTION 3: Composition/information on ingredients****3.1 Substances**

<b>BUTYL ACETATE -norm</b>	<b>25-40%</b>
CAS number: 123-86-4	EC number: 204-658-1
<b>Classification</b>	
Flam. Liq. 3 - H226	
STOT SE 3 - H336	

## 334-0026 VIP FAST ACRYL SEALER VARNISH

<b>TOLUENE</b>	<b>10-20%</b>
CAS number: 108-88-3	EC number: 203-625-9
<b>Classification</b>	
Flam. Liq. 2 - H225	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Repr. 2 - H361	
STOT SE 3 - H336	
STOT RE 2 - H373	
Asp. Tox. 1 - H304	
Aquatic Chronic 3 - H412	
<b>XYLENE</b>	<b>10-20%</b>
CAS number: 1330-20-7	EC number: 215-535-7
<b>Classification</b>	
Flam. Liq. 3 - H226	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Acute Tox. 4 - H312	R10 Xn;R20/21 Xi;R38
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
<b>ACETONE</b>	<b>10-20%</b>
CAS number: 67-64-1	EC number: 200-662-2
<b>Classification</b>	
Flam. Liq. 2 - H225	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Eye Irrit. 2 - H319	F;R11 Xi;R36 R66 R67
STOT SE 3 - H336	
<b>ETHYL ACETATE</b>	<b>5-10%</b>
CAS number: 141-78-6	EC number: 205-500-4
<b>Classification</b>	
Flam. Liq. 2 - H225	
STOT SE 3 - H336	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**Product name** 334-0026 VIP FAST ACRYL SEALER VARNISH

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. Get medical attention if any discomfort continues.
<b>Inhalation</b>	Move affected person to fresh air at once. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

## 334-0026 VIP FAST ACRYL SEALER VARNISH

<b>Ingestion</b>	Do not induce vomiting. Remove affected person from source of contamination. Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
<b>Skin contact</b>	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	Coughing, chest tightness, feeling of chest pressure. Nausea, vomiting. Exhaustion and weakness.
<b>Ingestion</b>	Nausea, vomiting. Drowsiness, dizziness, disorientation, vertigo.
<b>Skin contact</b>	Skin irritation.
<b>Eye contact</b>	Irritation of eyes and mucous membranes.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations.
-----------------------------	------------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Toxic gases/vapours/fumes of: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO). May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. Ventilate closed spaces before entering them. Move containers from fire area if it can be done without risk. Risk of re-ignition after fire has been extinguished. Do not use water jet as an extinguisher, as this will spread the fire.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation.

### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

## 334-0026 VIP FAST ACRYL SEALER VARNISH

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Avoid spilling. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Eliminate all sources of ignition. Eye wash facilities and emergency shower must be available when handling this product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m<sup>3</sup>

#### TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 191 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 150 ppm(Sk) 574 mg/m<sup>3</sup>(Sk)

#### XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m<sup>3</sup>(Sk)

#### ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

#### ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

### 8.2. Exposure controls

## 334-0026 VIP FAST ACRYL SEALER VARNISH

### Protective equipment



### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

### Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield.

### Hand protection

Use protective gloves.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.

### Hygiene measures

Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

### Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Slightly viscous liquid.
Colour	Colourless to pale yellow.
Odour	Characteristic.
Initial boiling point and range	>75°C @ 760 mm Hg
Flash point	< 23°C
Bulk density	0,97 ±0,05 g/cm <sup>3</sup> , 20C
Solubility(ies)	Insoluble in water.
Viscosity	45-55 s @ D4 / 20°C

### 9.2. Other information

Other information	No information required.
Volatile organic compound	This product contains a maximum VOC content of 690 g/l.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

### 10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
-----------	--

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not known.
------------------------------------	------------

### 10.4. Conditions to avoid

Conditions to avoid	Avoid heat. Avoid contact with the following materials: Oxidising agents. Reducing agents.
---------------------	--

## 334-0026 VIP FAST ACRYL SEALER VARNISH

### 10.5. Incompatible materials

**Materials to avoid** Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

**Other health effects** There is no evidence that the product can cause cancer.

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 110,000.0

#### Acute toxicity - inhalation

**ATE inhalation (gases ppm)** 450,000.0

**ATE inhalation (vapours mg/l)** 1,100.0

**ATE inhalation (dusts/mists mg/l)** 150.0

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Not available.

**Genotoxicity - in vivo** Not available.

#### Carcinogenicity

**Carcinogenicity** Not available.

#### Reproductive toxicity

**Reproductive toxicity - fertility** Not available.

**Reproductive toxicity - development** Not available.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** Not available.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not available.

### **General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

### **Inhalation**

Vapours may cause headache, fatigue, dizziness and nausea. Vapour may irritate respiratory system/lungs.

### **Ingestion**

Harmful: may cause lung damage if swallowed. Pneumonia may be the result if vomited material containing solvents reaches the lungs. Narcotic effect.

### **Skin contact**

Harmful: danger of serious damage to health by prolonged exposure in contact with skin.

### **Eye contact**

Irritating to eyes. Vapour or spray may cause temporary (reversible) eye damage.

### **Acute and chronic health hazards**

Swallowing concentrated chemical may cause severe internal injury.

### **Route of entry**

Inhalation Ingestion. Skin and/or eye contact

## 334-0026 VIP FAST ACRYL SEALER VARNISH

<b>Target organs</b>	Respiratory system, lungs
<b>Medical symptoms</b>	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
<b>Medical considerations</b>	Skin disorders and allergies.

### SECTION 12: Ecological Information

**Ecotoxicity** No data on possible environmental effects have been found.

#### 12.1. Toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: >100 mg/l, Fish

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: >100 mg/l, Daphnia magna

**Acute toxicity - aquatic plants** IC<sub>50</sub>, 72 hours: >100 mg/l, Algae

#### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

#### 12.4. Mobility in soil

**Mobility** The product is miscible with water and may spread in water systems.

#### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** No information required.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

### SECTION 14: Transport information

#### 14.1. UN number

**UN No. (ADR/RID)** 1263

**UN No. (IMDG)** 1263

**UN No. (ICAO)** 1263

**UN No. (ADN)** 1263

#### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** PAINT RELATED MATERIAL

**Proper shipping name (IMDG)** PAINT RELATED MATERIAL

**Proper shipping name (ICAO)** FLAMMABLE LIQUID, NOS

**Proper shipping name (ADN)** FLAMMABLE LIQUID, NOS



## 334-0026 VIP FAST ACRYL SEALER VARNISH

### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

#### Transport labels



### 14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

### 14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
<b>EU legislation</b>	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

## 334-0026 VIP FAST ACRYL SEALER VARNISH

**Guidance** Workplace Exposure Limits EH40.  
Introduction to Local Exhaust Ventilation HS(G)37.  
CHIP for everyone HSG228.  
Approved Classification and Labelling Guide (Sixth edition) L131.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

**Key literature references and sources for data** This SDS is prepared based on the information received from the product raw material.

**Revision comments** This is first issue.

**Issued by** Bahadır AKDAS

**Revision date** 12/05/2016

**Revision** 00

**Supersedes date** 12/05/2016

**SDS number** 20282

**Hazard statements in full** H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H361 Suspected of damaging fertility or the unborn child if swallowed.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.