



TECHNICAL DATA SHEET

Dök.No: ÜRT-TDS-284
Yay.Tar.: 05.06.2024
Rev. No : REVİZYON-00
Rev.Tar. : 05.06.2024
Sayfa : 1/1

PRODUCT**EXO-TEAK OIL****PRODUCT CODE**

808-0048

DESCRIPTION

Premium teak oil for regular maintenance of outdoor wooden surfaces and wooden garden furniture.

APPLICATION AREAS

It is used for regular maintenance, especially in outdoor wooden furniture, where simplicity and naturalness are at the forefront and where the texture of the wood is felt, in order to protect the wood without compromising its naturalness and warmth.

PROPERTIES

Easy applied
Penetrates deeply into the pores of the wood, nourishes and revitalizes it.
Provides a silky texture to the surface of the wood
Provides resistance to water.

TECHNICAL PROPERTIES

Appearance	Yellow to brown oil
Density (g/cm ³ ; 20°C)	0,8 - 0,9
Touch Dry (20°C, %50 humidity)	4 - 5 hr
Set Dry(20°C, %50 humidity)	24 hr

Drying time depends on the type of application.

DILUTION RATIO

Product in the can, is ready to used, no need any dilution.

APPLICATION METHOD:

The product should be mixed thoroughly in its packaging, and the application surfaces should be cleaned from all kinds of dust, oil and dirt. Old but unpainted and new wooden surfaces should be sanded with 80/120. Painted and polished surfaces should be applied after completely removing the old paint/varnish and removing all dust and dirt. The oil, which has been thoroughly homogenized by mixing (shaking), is applied undiluted to dry and clean wooden surfaces with a brush, roller or cloth, ensuring that the wood is thoroughly absorbed and impregnated, and the excess is wiped off with a clean cloth. Wait 24 hours for it to dry completely. It should not be used beforehand and should be kept under protection. Under normal conditions, application should be made at 15-25°C and 50±5% humidity, and should not be applied under direct sun and rain. Maintenance should be renewed every season, but the protection and maintenance period can be extended by covering the wooden surface when it is not in use.

When applied in a single layer, 12 - 15 m² area can be covered by 1 lt (except for losses), the fact that the depending on the application method.

STORAGE and PRECAUTIONS

The product can be stored up to 24 months in dry conditions (5 -25°C and 50±5%relative humidity) and in its original packaging.

It's recommended to read SDS before applications.

The cloths used in the application should be disposed of after being soaked in water in order to prevent any ignition.

Important Note: This information is based on our present state of knowledge and is intended to provide general notes on Kubilay Products and their uses. However without guarantee as conditions and methods of end users are beyond our control. We recommend that end users determine the suitability of the materials before adapting them on a commercial scale.